

EXTRAPOL CW60

Description

EXTRAPOL CW60 is a blend of selected waxes and release agents specifically formulated to provide an extremely effective release system for vertically formed concrete pipes cast on steel pallet rings.

Benefits

- Thixotropic in nature the product affords good vertical surface adherence.
- Fast drying system
- Eliminates the need for secondary release agents.
- Non-aggressive to rubber seals and expanded polystyrene sealing materials, e.g. pipe spigots.
- Minimal force required for removal of pallet rings.
- Minor cleaning only required prior to repeated casting.

Properties

Appearance:	Pale wax paste
Specific Gravity:	.0.800 @ 20°C
Flash Point:	30°C (PMCC)
Storage:	Indefinite in manufacturer's sealed drums.

Application

EXTRAPOL CW60 is supplied ready to use and should not be diluted. Should be brush applied to pallet rings. Pallet should be allowed to dry prior to casting. When concrete is cured the pallet ring can be removed with the minimum amount of force. Only light cleaning is required before the cycle can be repeated.

Coverage

10-15 m²/Kg

Limitations

EXTRAPOL CW60 is unsuitable for general precast requirements.

Packaging

EXTRAPOL CW60 is supplied in 20Kg sealed kegs.

Health and Safety

This product should be stored in manufacturer's sealed drums and kept away from naked flames, electrical equipment, foodstuffs and children. The product should be applied in a well ventilated area.

Additional information available from Health & Safety Data Sheet.