

SAFEBLOCKSEAL

High Performance Water Based Block Paving Sealer

DESCRIPTION

SAFEBLOCKSEAL is a water based, low odour, polyurethane acrylic dispersion specifically developed for sealing block paving.

SAFEBLOCKSEAL is a white, translucent liquid which forms a film after evaporation of the water. The film is clear and highly resilient. Heavy applications will cause the cured film to have a milky appearance.

Extended drying will allow the sealer to become clear.

BENEFITS

- Penetrates and seals block paving surfaces to protect against the effects of weathering.
- Dries to a clear transparent film that resists yellowing under exterior or ultraviolet exposure.
- Gives an alternative to solvent based materials where fumes may be objectionable, undesirable, or noncompliant.
- Suitable for use on other concrete or clay paving materials
- Improves cohesion of sand infill

INSTRUCTIONS FOR USE

Surface Preparation - The surface and joints should be clean and free of moulds, mildews or other plant growth. Remove any other materials such as oil or grease that may prevent adhesion of the **SAFEBLOCKSEAL**. Apply any weed control products according to instructions.

Avoid spraying near vehicles. Surfaces need not be dry but excessive dampness will reduce penetration.

Mixing - **SAFEBLOCKSEAL** should be used directly from the container.

Application - Apply at a uniform coverage by spray, brush or roller. **SAFEBLOCKSEAL** may be sprayed with a hand held "pump-up" sprayer or with an airless industrial sprayer. If roller applied, use a short 8-10mm nap sleeve.

Sealing - Generally a second coat will be required, apply within 24 hours.

Only apply sufficient **SAFEBLOCKSEAL** to give a seal without building a shiny surface that may be slippery in wet conditions.

CLEANING

Immediately after spraying, clean line and nozzle thoroughly with water.

Brushes and rollers can also be cleaned with water.

COVERAGE

	First Coat	Optional Second Coat
Sealing Block Paving	5-7 m ² /litre	7-9 m ² /litre

*Coverage rates assume dense blocks. Coverage will vary from the above rates depending on surface porosity and texture.

Eco-Friendly Concrete Release, Curing & Sealing

AVOID EXCESSIVE BUILD-UP. THICKER APPLICATIONS MAY LEAD TO DISCOLOURATION AND IMPROPER SEALER PERFORMANCE.

TECHNICAL INFORMATION

Typical Engineering Data

The following results were developed under laboratory conditions for a 0.1mm wet film.

Drying Time* at 20°C, 60% RH	1-2 hours
Recoat Time**	3-4 hours but <24 hrs
VOC Content	30g/l
Adhesion to clay blocks	ASTM D-4541 excellent
Weatherometer testing	
ASTM G-53, @ 500 hours	
Ultraviolet resistance	good
Chalk resistance	no chalking
Check/peel resistance	no deterioration

* Low surface or air temperatures and/or high relative humidity will extend drying times.

**Where a second coat is to be applied, application must be within 24 hours to ensure proper intercoat adhesion.

LIMITATIONS

Do not use in rain or if rain is expected in next 4 hours. Do not use in freezing temperatures. Suitable for most general applications but should not be used where persistent moisture is present.

PACKAGING

210, 25 and 5 litre containers.

STORAGE

Keep containers sealed. Store in dry conditions at room temperature and away from direct heat. Protect from frost. When stored correctly in unopened container storage stability is 2 years.

HEALTH & SAFETY

Avoid physical contact with material and inhalation. If contact with skin should occur wash with a suitable antiseptic cleaner and then soap and water. If splashes should affect eyes, bathe immediately with clean water and if discomfort persists seek medical advice.

Reference should be made to the separate **SAFEBLOCKSEAL** Health and Safety literature.