

EpoFloor Seal

Technical Specification



Adomast

Epoxy Resin Based Surface Sealer

EPOFLOORSEAL is a two pack, water dispersible, epoxy resin based system for use as a surface sealer. It will impregnate to strengthen the surface, protect it from accidental chemical spillage and act as a barrier against damp penetration

Advantages

Typical applications of EPOFLOORSEAL include:

- Sealing concrete and granolithic floors
- Sealing wall renders
- Sealing brick and block paving.

Appearance

Mixed material forms an emulsion with an off-white milky colour, which disappears after application to leave a clear transparent film.

Application

USE

Surface Preparation

Remove entirely any dust, oils or other deposits to leave clean sound surface. Any residual dampness will tend to hinder Sealer impregnation, therefore surfaces should preferably be dry.

Mixing

In a clean plastic bucket, or similar, mix the entire contents of both containers. Add 3 litres of clean water (smaller container = 1 litre) and continue mixing until completely dispersed.

Application

Immediately after mixing, brush the sealer on to the prepared surface, brushing in two directions at right angles to each other. It is important to spread the sealer as thinly as possible and not to permit pooling of material. Apply a second coat in similar manner only after any milky appearance of the first coat has completely disappeared but allowing not more than 18 hours between coats. On very porous surfaces additional coats may be necessary.

Do not apply in temperatures below 5°C.

Pot Life

This is influenced by temperature. In practice under normal conditions a pot life of approximately 60 minutes can be expected.

CureTime

Full cure is achieved after approximately 7 days at 20°C. Lower temperatures will prolong cure time but sealed surfaces will generally take light foot traffic the following day.

Cleaning of Equipment

Brushes and equipment should be washed thoroughly in clean water immediately after use and before material begins to set, followed by a rinse in RESO-KLENS.



Coverage

One 3.3Kg pack will seal up to 35m² per coat, dependent upon surface texture and porosity



Storage

Keep all containers sealed, store at room temperature and away from direct heat. Under normal temperate and dry conditions storage life is in excess of one year.



Shelf Life

Shelf life is minimum 12 months subject to storage temperature and humidity.



Specification

EpoFloor Seal supplied by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions.

For specific advice regarding any aspect of this product, please consult our Technical Department



Health and Safety

EPOFLOORSEAL should be handled carefully and skin contact, exposure to high vapour concentrations and ingestion avoided.

Wearing of overalls, gloves and protective eyewear should be considered together with the application of a suitable barrier cream to hands where necessary.

Reference should be made to the separate EPOFLOORSEAL Health and Safety literature.