



Technical Specification

Degreasing Fluid

ADOSOLVE is a non-caustic powerful solvent emulsion designed to remove oil, grease, wax, bitumen and other materials from a variety of surfaces. It can be used on concrete, stone, wood, steel, terrazzo and many other surfaces.

It can be diluted with water or spirit based material

Advantages

- Easy to apply by applicator or spray
- Quickly breaks down and removes contaminants
- Excellent penetration properties
- Easily removed by flushing with water.
- Contains bactericidal additive
- Inexpensive square metre coverage

Application

Application

Roll or shake drum prior to use.

Absorbent Surfaces

Brush well into surface, allow to react with contaminant, remove heavy surface build up with scraper and if necessary apply a second treatment.

Wash down with water after each application.

Non-absorbent Surfaces

Vehicles, machinery, plant, etc., brush surfaces thoroughly, agitating ADOSOLVE where possible before hosing down.

ADOSOLVE may be diluted with water or spirit before use.

For use on terrazzo : dilute only with water.

Coverage

Dependent on porosity of surface to be cleaned and extent and type of stain

Storage

Supplied in 5, 20, 25 and 205 litre containers. Keep the container closed when not in use. Store in a cool dry conditions between 5 and 25°C.

Shelf Life

Shelf Life is 12 months from date of manufacture

This information is based on experience and usage, however recommendations are made without warranty or guarantee, since the conditions of use are out of our control

Specification

Adosolve is manufactured & supplied by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department

Health and Safety

ADOSOLVE is not considered flammable. However, contact with the eyes and skin should be avoided. Should any contact occur, rinse the affected area thoroughly with plenty of water.

When handling ADOSOLVE it is recommended that plastic gloves and eye protection is worn. If ADOSOLVE is to be sprayed ensure adequate ventilation. The wearing of a simple face mask will minimise the risk of inhalation of mists and vapours.

In case of accidental splashing wash the affected area with copious amounts of clean water.

Please refer to the separate ADOSOLVE Health and Safety Data Sheet.