

Engine Coolant and Antifreeze

A glycol based concentrate suitable for use as an engine coolant and antifreeze

Suitable to be used all year round as an engine coolant with operating temperatures down to -35°C

Advantages

- Helps prevent winter freezing and summer boil over.
- Nitrite, Amine, Silicate and Borax free.
- Corrosion protection.
- May be used in diesel and petrol engines.
- Suitable for a wide range of modern heavy duty engines

Application

- Dilute with water, as recommended by your vehicle handbook.
- Systems should be drained, flushed and refilled.
- Spills should be soaked with oil absorbent granules, sand and then be washed with soapy water.
- Wash off any spillage on paintwork immediately.
- Check antifreeze regularly
- Replace every 2 years.
- Maximum concentration = 50% water / 50% antifreeze
- Appearance Clear liquid
- Specific Gravity @ 20 °C 1.1
- Boiling Point Min 150 °C

Storage

Keep stored in closed sealed containers and away from heat sources

Shelf Life

2 years from date of manufacture

Specification

Antifreeze Concentrated is manufactured by Adomast Manufacturing Ltd and shall be used in accordance with the manufacturer's instructions

Health and Safety

Avoid physical contact with material. Where contact with skin occurs wash with suitable antiseptic cleaner. If accidental contact with eyes occurs bathe immediately with copious quantities of clean water and immediately seek medical attention.

Reference should be made to the separate **Anti-freeze Concentrate** Health and Safety literature.