

Cleaning Solvent for Resin Based products

Resoklens is a specially formulated solvent for cleaning resin products from tools and equipment before the resin has hardened, and for removing any residual release agent from formwork.

Application

When removing resin from tools, clean with RESOKLENS immediately after use before the resin has hardened.

When removing any residual release agent from formwork, the surface should be wiped with a rag soaked in RESOKLENS.

When complete the surfaces should then be wiped over with a clean dry cloth. When using epoxy resin mortars, RESOKLENS should be used to wipe over the float face to assist in obtaining a good smooth finish.

Storage

RESOKLENS is based in a flammable solvent. Store in a cool, well ventilated area.

Keep container tightly closed. Keep away from sources of ignition.

Avoid any build-up of electrostatic charge in the immediate area. Ensure that lighting and electrical equipment nearby are not a source of ignition.

Shelf Life

12 months in sealed containers from date of manufacture. Must be used 2 months after opening.

Specification

RESOKLENS is manufactured by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department

Health and Safety

Prolonged physical contact should be avoided and personal and environmental hygiene encouraged in common with the use of all mould release agents. Where contact with skin occurs, the material should be removed with soap and water. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists, medical attention should be sought without delay.

See Safety Data Sheet for further information.