

Cleaning & Preservative For Scaffolding Clips & Fittings

Safclean has been formulated to be used in the cleaning of scaffold and other fittings. It quickly frees rusted threads to allow easy movement and leaves a light oily residue to reduce rusting in storage and use,

Application

Fittings should be cleaned of loose dust and any concrete adhering to them.

For light cleaning apply liberally by spray or brush.

For heavier cleaning, fully immerse in SCAFCLEAN and leave for 15 to 20 minutes. Agitate occasionally.

Remove and allow any excess SCAFCLEAN to drain back into the container. Check threads for free movement. (Fittings that are badly corroded may require a second or more applications)

Place in spillage and allow to dry before exposing to wet weather.

Where long or exposed storage is anticipated treat with Adoshield Premium.

Coverage

Approximately 3-5m² per litre.

Storage

SCAFCLEAN is based in a flammable solvent. Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Avoid any build-up of electrostatic charge in the immediate area. Ensure that lighting and electrical equipment nearby are not a source of ignition.

Shelf Life

12 months in sealed containers from date of manufacture. Must be used 2 months after opening.

Specification

SCAFCLEAN is manufactured by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department

Health and Safety

During application avoid contact with eyes and skin. In the event of eye contact irrigate immediately with copious quantities of water and then seek medical advice. In the event of skin contact wash with soap and water, or resin removing cream.

See Safety Data Sheet for further information.